

型号		CXAH/CGAH 0105C	CXAH/CGAH 0125C	CXAH/CGAH 0165C	CXAH/CGAH 0205C	CXAH/CGAH 0245C	CXAH/CGAH 0305C	CXAH/CGAH 0405C
附加选项(第14·15位代码)		RJ	RJ	RK	RK	RK	RL	RL
制冷能力	Kal/Hr	21,500	26,060	32,850	43,000	51,600	66,910	89,440
	kW	25	30.3	38.2	50	60	77.8	104
制热能力	Kal/Hr	24,100	28,040	38,270	46,440	53,320	72,580	99,760
	kW	28	32.6	44.5	54	62	84.4	116
电源		380-415V/50Hz/3φ						
压缩机	形式	全封闭涡旋式高效压缩机						
	数量	2	2	2	4	4	2	2
	输入功率(制冷/制热)(kW)	8.4/8.1	9.6/9.9	11.7/13.7	15.7/15.7	19.0/18.3	23.1/24.9	32.5/34.7
	运行电流(制冷/制热)(A)	16/15.6	17.2/18	21.6/25.6	30/30	34.8/33.6	44.8/47.2	56.0/59.0
	启动电流(A)	58	74	98	131	148	175	230
风扇(轴流式)	外径(mm)	712	712	712	712	712	805	900
	数量	1	1	2	2	2	2	2
	额定功率(kW)	0.56	0.56	1.12	1.12	1.12	3.34	4
	转速(RPM)	550	550	550	550	550	720	720
	风量(CMH)	10600	10600	17,500	21,200	21,200	30,000	40,000
冷冻水泵	型式	多段离心泵						
	输入功率(kW)	0.7	1.0	1.4	1.4	2.4	2.4	2.4
	机外扬程(mH2O)	17	19	19	21	25	23	19
蒸发器	型式	板式换热器						
	流量(制冷/制热)(L/min)	71.7/80.2	86.8/93.5	109.5/127.6	143/154.8	172/177.7	223/242	298/332
保护装置		过热保护·高低压开关·防冻开关						
冷冻油	型号	3GS	SONTEX200LT	160P	SONTEX200LT	SONTEX200LT	160P	ISO68-320SZ
	填充量(L)	2×1.2	2×1.7	2×3.3	4×1.8	4×1.7	2×6.6	2×8
冷媒	型号	R22						
	填充量(Kg)	2×3.7	2×3.7	2×7.8	2×7.2	2×7.5	2×16/2×12	2×18/2×14
外形尺寸	高度(mm)	1137	1137	1137	1137	1137	1585	1640
	宽度(mm)	1300	1300	2375	2375	2375	2600	2600
	深度(mm)	965	965	1118	1118	1118	1200	1200
噪声值	dB(A)	63.0	64.0	64.0	66.0	66.5	74.0	73.5
进出水管φ(PT)		1-1/4"(内)	1-1/4"(内)	1-1/2"(内)	1-1/2"(内)	1-1/2"(内)	2"(外)	2"(外)
运行重量(Kg)		295	300	495	530	530	630	980

获取更多

CXAH/CGAH 0505C	CXAH/CGAH 0605C1NMA
RL	RL
113,520	135,880
132	158
116,960	151,360
136	176

2	2
40.2/41.5	47/50.6
69/75	77.6/82.2
270	320
800	900
3	3
4.59	2.00
920	705
58,500	75,000

3.1	3.15
21	21

378/390	453/505
---------	---------

ISO 68 - 320SZ	POE-320SZ
2 x 8	2 x 8

2 x 24/2 x 20	2x31/2x26
1740	1740
3010	3250
1360	1360
73.1	78.6
2-1/2" (内)	2-1/2" (内)
1070	1256

获取更多资料 微信搜索蓝领星球